



SKIRON-X



Tactical Unmanned Aircraft System

OPTIMIZED FOR SIMPLE AND EFFECTIVE ISR MISSIONS

The Skiron Expeditionary sUAS combines the simple operation of an electric vertical take-off and landing (eVTOL) configuration with the longer endurance of a fixed-wing design. It has a range of up to 75 km, and an EO/IR camera payload provides precise ground resolution for airborne intelligence, surveillance, and reconnaissance (ISR).



Hybrid VTOL fixed-wing

Launch and land without auxiliary equipment. Lift rotors enable vertical launch and landing, while the fixed wing design allows for longer flight time.



Simplified operations

Engineered for operation by non-pilot personnel. User-friendly mission planning software facilitates rapid training and allows for mission adjustments even during flight.



Flexible payload

Modular nosecone design, enabling swift payload changes and customized integrations. EO/IR, EW, communications relay, lethal systems payload agnostic.



Long endurance

Flight endurance exceeds 3.5 hours on standard battery power.



Small footprint

Designed for efficient deployment. Transportable by standard pick-up truck with a two-person crew. Supports mobile missions using an omni-directional antenna.



Autonomy

Implementation and integration of behaviors to support any payload. Advanced autonomy enhances aircraft capabilities without requiring extensive operator training.

Attributable cost model with streamlined procurement options. Contact us for more information, existing IDIQ procurement mechanisms available for expedited acquisition.

AIRCRAFT SPECIFICATIONS

SKIRON-X

Length	2.2 m
Wingspan	5.0 m
Propulsion system	40Ah Li-ion rechargeable battery
Max Payload	2.26 kg
Takeoff weight	23.4 kg with Trillium HD55 and battery
Flight endurance	3.5 hours
Max speed	26 m/s / 50 knots
Cruise speed	19 m/s / 36 knots
Max cruise altitude	3658 m density altitude
Typical operating altitude	152 m - 1219 m AGL
Navigation	Anti-jam GPS/GNSS solution available.
Payload attachments	One standard nose mount; optional belly mount

SYSTEM SPECIFICATIONS

Aircraft container size	0.66 m x 0.61 m x 2.39 m
Aircraft container weight	82 kg
Setup time	10 min
Integrated payload	Trillium gimbals, HD25 to HD55. Custom integration available.

GROUND CONTROL STATION SPECIFICATIONS

Software	Kutta UGCS software
Size + Weight	16 kg / 483 mm (L) 381 mm (W) 203 mm (D)
Networking	Wired or wireless
Range of Operations	Integrated Silvus radio with dual omni attachment. Ethernet/IP/ RF interface to connect to long range antenna
Display	Two Toughbooks: 355.6 mm monitor and 396.2 mm sunlight-readable monitor
Handheld (optional)	KTAC capable. Can be worn as a chest mounted device, placed in a pocket, or held with one hand. Compatible with the Android Tactical Assault Kit (ATAK).

DATA LINK SPECIFICATIONS

Datalink standard	Silvus SC4200EP <i>Blue UAS Framework Certified</i>
C2 link range	6 km with 1W radio and omni ant; 75 km with 10W radio and tracking
Frequency	S-band; customizable dual S & C bands
Link rate	Up to 20 Mbps
Output power	Up to 10 W
Standard Encryption	AES256; FIPS 140-3 Level 2 <i>LPI/LPD and Anti-Jam Options Available</i>

INTEROPERABILITY

ATAK interoperability	Custom payload integration capable	MISB compatible live video with KLV metadata	Aided target recognition capable	Built on MOSA principles, ensuring transparency and modularity.
-----------------------	------------------------------------	--	----------------------------------	---

